Metal to metal abrasion resistant

GH350R

JIS Z 3251 DF2A-350R

Product Features:

- Weld metal typical hardness approximately HRC35.
- High welding performance, low spatter loss and good bead appearance.
- Good cutting workability.

Applications:

 Suitable for hardfacing repair welding of machinery; carbon steel, cast iron and hardenable alloy steel repair and fabrication welding.

| Typical chemical composition of all-weld metal(wt%) | | | | | | | | |
|---|------|------|------|------|--|--|--|--|
| С | Si | Mn | Cr | Мо | | | | |
| 0.11 | 0.37 | 0.86 | 2.37 | 0.63 | | | | |

| Typical hardness of weld metal | | | | | | |
|--------------------------------|--------|--|--|--|--|--|
| As welded HRC | layers | | | | | |
| 36 | 3 | | | | | |

| Size (mm) & recommended welding parameters (A) | | | | | | | |
|--|---------|---------|---------|-------------|---------|--|--|
| Diameter / Length | 2.6/300 | 3.2/350 | 4.0/400 | 5.0/350/450 | 6.0/450 | | |
| Flat position | 70~100 | 100~140 | 140~190 | 180~230 | 240~300 | | |

Note:

- 100~120°C x 1 hr baking prior to use.
- Keep short arc length while welding.
- 150°C preheating temperature on base metal before welding.



Goodweld Corporation No.99, Huangong Rd. Yongkang Tainan, Taiwan Phone: 886-6-2331003 Fax: 886-6-2333213 All Right Reserved